



Strategy Planning of Plastic Material

PC Glass Fiber Composite - PC+ 30%GF Grade: C30G

項目 Property	單位 Units	方法 Test Method	數值 Value
Specific Density	比重	D-792	1.4
Filler Content	填充物含量	%	30%
Tensile Strength	抗張強度	kgf/cm ²	D-638 1300
Tensile Elongation	延伸率	%	D-638 5
Flexural Strength	彎曲強度	kgf/cm ²	D-790 1800
Flexural Modulus	彎曲模數	kgf/cm ²	D-790 74000
Izod impact Strength	衝擊強度	kgf cm/cm	D-256 14
1/8" bar with notched	(有缺口)		
Melt Index	融溶指數	g/10min	D-1238 6
Shrinkage	收縮率	%	D-955 0.1-0.3
Description	產品描述	30%GF Reinforced	30%玻璃纖維補強

☆上表所列數據資料僅供參考用

These property values under specific test conditions as defined in the table above are for reference only.

揚智企業有限公司 YANPLA INDUSTRIAL CO.,L.T.D TEL:886-2-26039888 FAX:886-2-26039887

台北縣林口鄉湖北村後湖52-16號 NO.52-16 HOU HU HU-PEI VILLAGE LIN KOW SHARUNG TAIPEI SHEIN TAIWAN, R.O.C.