

PA66 Super Tough Composite -PA66 Super Tough Reinforced
Grade: NT220N,NT220B

項目 Property	單位 Units	方法 Test Method	數值 Value		
			NT220N	NT220B	
			NT220N	NT220B	
Specific Density	比重		D-792	1.35	1.35
Filler Content	填充物含量	%		-	-
Tensile Strength	抗張強度	kgf/cm ²	D-638	460	420
Tensile Elongation	延伸率	%	D-638	85	110
Flexural Strength	彎曲強度	kgf/cm ²	D-790	530	480
Flexural Modulus	彎曲模數	kgf/cm ²	D-790	15000	14000
Izod impact Strength	衝擊強度	kgf cm/cm	D-256	120	120
1/8" bar with notched	(有缺口)				
Melt Index	融溶指數	g/10min	D-1238	-	-
Shrinkage	收縮率	%	D-955	-	-
H.D.T. (66 Psi)	熱變形溫度	°C	D-648	140	141
Rockwell Hardness	洛氏硬度	R-scale	D-785	D73	D73
Description	產品描述		Super Tough Reinforced	本色 高耐衝擊	黑色 高耐衝擊

☆上表所列數據資料僅供參考用

These property values under specific test conditions as defined in the table above are for reference only.

揚智企業有限公司 YANPLA INDUSTRIAL CO.,L.T.D TEL:886-2-26039888 FAX:886-2-26039887

台北縣林口鄉湖北村後湖52-16號 NO.52-16 HOU HU HU-PEI VILLAGE LIN KOW SHARUNG TAIPEI SHEIN TAIWAN, R.O.C.